

Prepared For:
ESCAMBIA COUNTY FLORIDA
purchasing department
PO Box 1111
Pensacola, FL 32591-1100
(850)436 - 5711
Reference ID: N/A

Presented By:
WARD INTL TRUCKS INC.
Kenny r Necaise
5885 NORTH W STREET
PENSACOLA FL 32505 -
(850)474-9301

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2016 5900i SBA 6X4 (DF697)

APPLICATION:	On-Off Highway Tractor - General
MISSION:	Requested GCWR: 80000. Calc. GVWR: 59200 Calc. Start / Grade Ability: 20.10% / 2.27% @ 55 MPH Calc. Geared Speed: 76.9 MPH
DIMENSION:	Wheelbase: 202.00, CA: 128.00, Axle to Frame: 60.00
ENGINE, DIESEL:	{Navistar N13} EPA 2010, SCR, 475 HP @ 1700 RPM, 1700 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 475 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, With Lube Pump, With Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 5.38
CAB:	Conventional
TIRE, FRONT:	(2) 11R24.5 HSR2 (CONTINENTAL) 476 rev/mile, load range H, 16 ply
TIRE, REAR:	(8) 11R24.5 HSR2 (CONTINENTAL) 476 rev/mile, load range H, 16 ply
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson HAS-460-55} 55" Axle Spacing; 46,000-lb Capacity, 9.5" Ride Height, With Shock Absorbers Mounted Inboard
PAINT:	Cab schematic 100KE Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
DF69700	Base Chassis, Model 5900i SBA 6X4 with 202.00 Wheelbase, 128.00 CA, and 60.00 Axle to Frame.
1616	FRAME RAILS WITH TAPERED REAR
1CCV	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" x 389.4" OAL
1LRC	BUMPER, FRONT Full Width, Heavy Duty, Chrome Plated Steel With H.D. Crossmember and Tow Pin
2ASG	AXLE, FRONT NON-DRIVING {Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity
	<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.
3ADD	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 14,000-lb Capacity; With Shock Absorbers
	<u>Includes</u> : SPRING PINS Threaded
	<u>Notes</u> : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.
4092	BRAKE SYSTEM, AIR Dual System for Tractor Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : DUST SHIELDS, FRONT BRAKE With 04092 Tractor Air Brakes and 16.5" Brakes : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab : HAND CONTROL VALVE, AIR Mounted on Steering Column : HOSE TENDER Back of Cab Mounted : PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel : PARKING BRAKE VALVE Combination Valve for Tractor and Trailer : QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle : SLACK ADJUSTERS, FRONT Automatic : SLACK ADJUSTERS, REAR Automatic : SWITCH, AUXILIARY Interrupter for Cab and Trailer Clearance/Marker Lights (Blinks Lights with Headlight Switch in "ON" Position); Instrument Panel Mounted : TRACTOR PROTECTION VALVE
	<u>Notes</u> : Rear Axle is Limited to 40,000-lb GAWR with Code 04092 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered.
4196	BRAKES, FRONT, AIR CAM 16.5" x 5", Includes 24 Sqn Long Stroke Brake Chambers
4732	DRAIN VALVE {Berg} Manual; With Pull Chain, for Air Tank
4764	DUST SHIELDS, REAR BRAKE for Use With Tractor Air Brakes
4774	SPECIAL RATING, GAWR Provides Rear Tractor Brake Rating Equal to Axle Rating up to 23,000-lbs for Single Axles, 46,000-lbs for Tandem Axles, or 69,000-lb for Tridem
	<u>Notes</u> : Provides Rear Axle GAWR Up to 46,000-Lb.
4AAU	BRAKE CHAMBERS, ADDITIONAL (2) {Bendix} Spring Brake Type; 30/30 Sqn
4AZU	AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (6-Channel 6 Sensor/6 Modulator)
	<u>Includes</u>

<u>Code</u>	<u>Description</u>
	: BOB TAIL PROPORTIONING SYSTEM for Rear Axles is Included With 04092, BRAKE SYSTEM, AIR (Tractor) When Ordered With Code 04AZG, ABS OMIT ITEM
4EAH	AIR DRYER {Bendix AD-9} With Heater, Standard Location
	<u>Includes</u> : AIR DRYER LOCATION Inside Left Rail, Back of Cab
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Spring Brake
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn
4LAA	SLACK ADJUSTERS, FRONT {Haldex} Automatic
4LGA	SLACK ADJUSTERS, REAR {Haldex} Automatic
4NDH	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 8.625" Includes 30/30 Sq.In. Long Stroke Brake Chambers and Spring Actuated Parking Brake
	<u>Notes</u> : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.
4SPM	AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM Capacity, Single Cylinder
4WBX	DUST SHIELDS, FRONT BRAKE for Air Brakes
5710	STEERING COLUMN Tilting and Telescoping
5PSA	STEERING GEAR {Sheppard M-100} Power
5WBC	STEERING WHEEL {V.I.P.} 2-Spoke; 18" Diam., Black, Leather Wrapped
6DDC	DRIVESHAFT SYSTEM SPL250XL Driveshaft and SPL170XL Inneraxle Shaft in lieu of 1810 Driveshaft and 1710 Inneraxle Shaft
7BES	AFTERTREATMENT COVER Polished Aluminum
7DXM	EXHAUST SYSTEM Switchback Horizontal Aftertreatment Device, Frame Mounted Right Side Under Cab; Includes Dual Vertical Tail Pipes & Bright Guards, Cab Mounted
7SDK	ENGINE COMPRESSION BRAKE by Jacobs; for N13 Engines, With Selector Switch and On/Off Switch
7WBB	TAIL PIPE (2) Turnback Type, Bright, for Dual Exhaust
7WBU	EXHAUST HEIGHT 11' 6"
7WZY	SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, ON/OFF Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in ON Position
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u> : BATTERIES (3) Maintenance-Free, 12-Volt 1950 CCA Total : CIGAR LIGHTER Includes Ash Cup, Center Console Mounted : FUSES, ELECTRICAL SAE Blade-Type : HAZARD SWITCH Integral with Turn Signal Switch : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : HEADLIGHTS (2) Sealed Beam, 5" x 7" Rectangular : HORN, AIR Single, Chrome : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : READING LIGHT, CAB (2) with Individual Switches; One Above Each Door : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : TURN SIGNAL FLASHER : TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature

<u>Code</u>	<u>Description</u>
	: TURN SIGNALS, FRONT Includes Integral Reflectors and Side Marker Lights; Fender Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature, Instrument Panel Mounted : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WIRING, CHASSIS Color Coded and Continuously Numbered
8559	LIGHT, WORK Pedestal Mounted BOC, With Switch on "B" Pillar Behind Driver's Seat
	<u>Notes</u> : Feature Included with Sleeper Cab or Frame Access Packages. : Feature Included with Sleeper Cab.
8649	FOG LIGHTS (2) {Per-Lux 600 Series} 100 Watt Sealed Beam, Clear, With Rectangular Lens and Louvers
	<u>Notes</u> : Fog Lights are Not Driving Lights
8695	SNOW SHIELD (2) Chrome; for Dual Air Horns
8718	POWER SOURCE Cigar Type Receptacle without Plug and Cord
8836	HORN, AIR (2) Single Bell, Extra Long, Organ Tone; Chrome
8GGN	ALTERNATOR {Bosch LH160} Brush Type, 12 Volt 160 Amp. Capacity, Pad Mount
8MKY	BATTERIES (3) {International Group 31} Maintenance-Free (3) 12-Volt 2775CCA Total
8RBZ	SPEAKER, AUXILIARY, CB RADIO With Jack for CB; Mounted Left Side Above Driver's Door
8RDH	ANTENNA BASE (2) Dual Function, for CB and Entertainment Radio, With Splitter, Lead-Ins and Dual Function Antennas; Mounted on Left and Right Mirrors
	<u>Includes</u> : CB WIRING for Mounting CB; in Center Header Storage Compartment
8RDT	CB RADIO Accommodation Package; Accommodates Larger CB Radio, Includes Brackets and Velcro Straps, With Two Post Power Terminal and Direct Wire Power Option Mounted Center of Header
8RMB	RADIO AM/FM/CD/WB/Clock/Bluetooth/USB Input/3MM Auxiliary Input, MP3, Apple Device Play & Control, Bluetooth for Phone & Music, with Multiple Speakers
8VAY	HORN, ELECTRIC Disc Style
8VUH	BATTERY BOX COVER Polished Aluminum
8WBW	JUMP START STUD Remote Mounted
	<u>Includes</u> : JUMP START STUD Mounted to Battery Box
8WDG	BACK-UP ALARM {Preco 1059} Electronic; Solid State, Dual Function, 112 dBA
8WKE	BATTERY BOX Aluminum With Aluminum Cover, 30" Wide, 2, 3 or 4 Battery Capacity, Mounted Left Side Under Cab
8WNH	RUNNING LIGHT (2) Daytime
8WNT	CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Mounted on Sunshade
8WXG	STARTING MOTOR {Mitsubishi Electric Automotive America 105P} 12-Volt, with Soft-Start
	<u>Notes</u> : This starter is designed to work reliably without the need for thermal overcrank protection and provides the same warranty coverage as starters with thermal overcrank protection.
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses

<u>Code</u>	<u>Description</u>
8XAK	SWITCH, MARKER INTERRUPT Interrupter; for Cab and Trailer Clearance/Marker Lights; Dual Position (Blinks Lights with Headlight Switch in "ON or OFF" Position)
8XAZ	TURN SIGNAL SWITCH {Douglas} Self-Cancelling Includes Integral Hazard Switch and Lift to Dim Feature
9107	FRONT END Tilting, Fiberglass
	<u>Includes</u>
	: GRILLE Stainless Steel Vertical Grille Bars
	: GRILLE SURROUND Polished Stainless Steel
	: HEADLIGHT BEZELS Chrome
9505	QUARTER FENDERS for Rear Wheels, Mirror-Finished Stainless Steel, Frame Mounted
9HAN	INSULATION, UNDER HOOD for Sound Abatement
9HBN	INSULATION, SPLASH PANELS for Sound Abatement
9WAC	BUG SCREEN Front End; Mounted Behind Grille
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u>
	: PAINT SCHEMATIC ID LETTERS "KE"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
10930	KEYS - ALL ALIKE, ID Variation F, K-100
10943	KEYS - ALL ALIKE Fleet - Includes Ignition and Cab Door Keys
10HJB	FIFTH WHEEL, AIR SLIDE {Fontaine SL7LWB725024} 24" Slide, Cast Top Plate, 7.25" Above Top of Frame; Left Side Release
10WCY	SAFETY TRIANGLES
10WPT	MUD FLAP HOLDER Spring Loaded, Painted Black; With 45-Degree End, With Red and White Reflective Tape; Less Flaps
10WPZ	MUD FLAPS, REAR Black Poly, Anti-Sail, Anti Spray, Less Logo; Less Holders
11001	CLUTCH Omit Item (Clutch & Control)
12BCT	ENGINE, DIESEL {Navistar N13} EPA 2010, SCR, 475 HP @ 1700 RPM, 1700 lb-ft Torque @ 1000 RPM, 2100 RPM Governed Speed, 475 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed
	<u>Includes</u>
	: FAN Nylon
12UNC	FEDERAL EMISSIONS EPA, OBD and GHG Certified for Calendar Year 2015; N13 Engines
12VBT	AIR CLEANER Single Element, Heavy Duty
	<u>Includes</u>
	: AIR CLEANER with Vacuator
	: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted
12VGA	ENGINE CONTROL, REMOTE MOUNTED for PTO with N13 Engines
12WCX	HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type
12WEG	COLD STARTING EQUIPMENT Automatic; With Engine ECM Control
12WTA	FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

<u>Code</u>	<u>Description</u>
12WUJ	COOLANT FILTER for 2010 N13 Engines
12WZB	EMISSION COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood
12XAV	RADIATOR Aluminum; Welded, Front to Back Down Flow System, 1429 SqIn, 740 SqIn CAC, 1099 SqIn 3 Core LTR
13ATR	TRANSMISSION, AUTOMATIC {Allison 4000_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hw; Includes Oil Level Sensor, With PTO Provision, Less Retarder
13TKT	LOCATION, PTO, SPLIT SHAFT With Front PTO Output Shaft Mounted 48" BOC and 11.5" Above Top of Frame
13WBL	TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission
13WCU	OIL COOLER, AUTO TRANSMISSION {Modine} Remote Mounted; For Use With Automatic Transmission Less Retarder
13WLM	TRANSMISSION OIL Synthetic; 63 thru 76 Pints
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction
13WYU	SHIFT CONTROL PARAMETERS Allison 3000 or 4000 Series Transmissions, 5th Generation Controls, Performance Programming
14862	PDL WARNING BUZZER Power Divider Lock
14899	SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab
14HRL	AXLE, REAR, TANDEM {Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, With Lube Pump, With Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 5.38
	<u>Includes</u> : POWER DIVIDER LOCK Air Operated, Cab Control with Indicator Light in Cluster : REAR AXLE DRAIN PLUG (2) Magnetic, For Tandem Rear Axle
	<u>Notes</u> : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires. : When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance
14ULT	SUSPENSION, REAR, AIR, TANDEM {Hendrickson HAS-460-55} 55" Axle Spacing; 46,000-lb Capacity, 9.5" Ride Height, With Shock Absorbers Mounted Inboard
	<u>Includes</u> : CROSSMEMBER, SUSPENSION 3-Piece
	<u>Notes</u> : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.
14WBN	DIFF. SWITCH CONTROLS Two Independent Switches for Control Traction Differentials on Tandem Rear Axles, Mounted on Dash
14WMK	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 65 thru 89.99 Pints
15BAA	DEF TANK COVER Stainless Steel
15DXD	FUEL TANK (2) Polished Aluminum, 24" Diam., 80 U.S. Gal., 302L Capacity; Total Capacity 160 U.S. Gal., 604L; with Dual Supply & Return Lines and Less Equalizer Line, Mounted Left & Right, Back of Cab
15DYR	DEF TANK 9.5 U.S. Gal. 36.0L Capacity, Frame Mounted Outside Left Rail, Back of Cab
15LKU	FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor

<u>Code</u>	<u>Description</u>
15WCS	FUEL COOLER Less Thermostat; Mounted in Front of Cooling Module
16031	CAB Conventional <u>Includes</u> : CLEARANCE/MARKER LIGHTS (5) Roof Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CONSOLE, CENTER Plastic, Driver Convenience with a Cup and Change Holder, Ash Tray and Lower Storage Area with Net. NOTE: Ash Tray not included with automatic transmission : DOME LIGHT, CAB (2) Rectangular, Door and Header-Mounted Switch Activated; Above Door Mounted, One Each Side : DOOR CHECK STRAP (2) One Each Door : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (2) One Each Side : GRAB HANDLE, EXTERIOR (2) Mounted Behind Driver and Passenger Doors : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : SKIN Riveted : STEP (4) Two Steps Per Door : STORAGE, CAB INTERIOR Vinyl Pocket, Mounted on Driver and Passenger Seat Back
16564	HEATER SHUT-OFF VALVES (1) Ball Check Valve Type, Supply Line
16CDL	CAB INTERIOR TRIM ACCENT Dark Tan
16HBJ	GAUGE CLUSTER Black Face; English with English Electronic Speedometer and with Tachometer for Air Brake Chassis, Includes Odometer, Trip Odometer, Total Engine Hours, and Trip Hours <u>Includes</u> : GAUGE CLUSTER (4) Water Temperature (Electronic), Engine Oil Pressure (Electronic), Fuel, Voltmeter
16HGG	GAUGE, OIL TEMP, ENGINE
16HGH	GAUGE, OIL TEMP, ALLISON TRAN
16HGL	GAUGE, OIL TEMP, REAR AXLE
16HGN	GAUGE, AIR APPLICATION
16HHG	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} With Chrome Bezel Mounted in Instrument Panel
16HHK	GAUGE, LOAD INDICATING With Chrome Bezel; for Use With Rear Air Suspension
16HHY	GAUGE, MANIFOLD PRESSURE Data Link Driven; With Chrome Bezel, Mounted in Instrument Panel, Includes Controller Module
16HLJ	GAUGE, DEF FLUID LEVEL
16JPG	SEAT, DRIVER {National 2000 Model 195} Air Suspension, Hi Back, Vinyl W/Cloth Insert, 2 Arm Rests, Isolator, Adjuster, 3 Chamber Lumbar, 6 Way Front Adj, 3 Way Rear Cushion Adj, 2-15 Degree Back Angle Adjustment, Adj Side Bolster, Vinyl Suspension Cover, Heat <u>Includes</u> : SEAT BELT 3-Point, Lap and Shoulder Belt Type <u>Notes</u> : Color Will Match Interior Trim Accent Color.
16PNU	SEAT, PASSENGER {National 2000 Model 192} Non-Suspension, High Back, Vinyl With Cloth Insert, 2 Arm Rests, 11 Degree Back Angle Adjustment, Map Pocket <u>Includes</u> : SEAT BELT 3-Point, Lap and Shoulder Belt Type <u>Notes</u> : Color Will Match Interior Trim Accent Color.

<u>Code</u>	<u>Description</u>
16SDG	MIRROR, CONVEX, LOOK DOWN {Lang Mekra} Right Side; 6" x 10 1/4", With Bright Finish
16VAJ	CAB INTERIOR TRIM Premium Level; Vinyl, for Day Cab <u>Includes</u> : "A" PILLAR COVER Plastic, Medium Tan : CAB INTERIOR TRIM PANELS Soft Padded Vinyl : CONSOLE, OVERHEAD Molded Plastic with Three Storage Pockets; One with Velcro Strap for CB Radio Mounting; Two with Netting; Light Switches for Dome and Courtesy Lights : COURTESY LIGHT (2) Driver and Passenger Door Mounted : DOOR TRIM PANELS Vinyl Covered Driver and Passenger Doors : FLOOR COVERING Rubber, Black : FLOOR MATS, CAB Rubber : HEADLINER Soft Padded Vinyl : HEATER BOX Metal, Painted Black : INSTRUMENT PANEL TRIM Vinyl, Medium Tan with Woodgrain Appearance Panel Face : MIRROR, CONVEX, LOOK DOWN Black Finish; 6" x 10-1/4"; Located on Passenger Side : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door : SUN VISOR (2) Vinyl with Toll Ticket Strap
16VAW	STORAGE, CAB INTERIOR Molded Holder for Thermos, Maps, and CD's; Located at Base of Passenger Seat <u>Notes</u> : Feature included with CAB INTERIOR TRIM, Eagle
16VRT	HEATER, ENHANCED CIRCULATION {Bergstrom} Control, for Extreme Cold Weather Climates
16VRZ	CAB SOUND INSULATION {Whisper Cab} Daycab Interior Noise Reduction Package
16WAK	WINDOW, POWER (2) in Left and Right Doors
16WJC	APADS SYSTEM {Index Sensors & Controls} Air Conditioner Protection and Diagnostics System; Use With Temperature Controlled Fan
16WJG	CAB DOOR LOCKS Power
16WKB	AIR CONDITIONER {International Blend-Air} With Integral Heater & Defroster <u>Includes</u> : HEATER HOSES Premium : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps : REFRIGERANT Hydrofluorocarbon HFC-134A
16WKR	WINDSHIELD Single Piece
16WLD	CAB REAR SUSPENSION {Link Z9079D1} Dual Frame Mounted Cab Rear Air Suspension; Includes Special Crossmember Assembly
16WSP	MIRRORS (2) {International} West Coast Type, Rectangular, Power Both Sides, Heated Heads, Lighted Both Sides, Bright Heads & Brackets, 16" x 7" & Convex, 102" Inside Spacing,
16XWE	SUNSHADE, EXTERIOR Bright Finish; Includes Integral Clearance/Marker Lights
16ZDV	GRAB HANDLE Exterior; Towel Bar Type In Lieu Of Non-Bright Grab Handles; for use with Cab/Frame or Cab/Frame/Sleeper Non-Bright Access, Without Chassis Skirts
16ZHG	ACCESS, CAB AND FRAME Bright, Frame Access Step Mounted Left Side, with One Deck Plate and Grab Handle
27DMJ	WHEELS, FRONT DISC; 24.5" Non-Polished Aluminum, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs <u>Notes</u> : Aluminum Wheels not Painted or Coated : Compatible Tire Sizes: 11R24.5, 12R24.5, 275/80R24.5, 285/75R24.5

<u>Code</u>	<u>Description</u>
28DRM	WHEELS, REAR DUAL DISC; 24.5" Painted Steel, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With .472" Thick Increased Capacity Disc and With Steel Hubs
29WLA	WHEEL BEARING, FRONT, LUBE (EmGard 50W) Synthetic Oil
7384225415	(2) TIRE, FRONT 11R24.5 HSR2 (CONTINENTAL) 476 rev/mile, load range H, 16 ply
7384225415	(8) TIRE, REAR 11R24.5 HSR2 (CONTINENTAL) 476 rev/mile, load range H, 16 ply
808WCU	STOP, TURN, TAIL & B/U LIGHTS (Truck Lite Super 44) Less Power Module; With L.E.D. Bulbs for Stop, Turn & Tail Lights and Super 40 Back Up Light; Must Include Separate Rear Reflectors
810000	FIFTH WHEEL LOCATION On Rear Axle Centerline
812BAG	FAN OVERRIDE Manual; With Electric Switch on Instrument Panel, (Fan On With Switch On)
813WCC	PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Control Valve, Piping and Wiring, Wired for PTO
816UAG	WINDOW, REAR 52.25" Wide
829WAD	WHEEL GUARDS, FRONT (Accuride) for Metric Hub Piloted Wheels with Flanged Mounting Nuts Mounted Between Hub and Wheel
829WAE	WHEEL GUARDS, REAR (Accuride) for Metric Hub Piloted Wheels with Flanged Mounting Nuts, Mounted Between Hub & Wheel and Between Dual Wheels

Services Section:

40118	WARRANTY Standard for Paystar 5000, and Workstar 7500/7600, Effective with Vehicles Built January 2, 2015 or Later, CTS-2003Z
1	install 2 line wetline kit with hot shift pto for a walking floor trailer



INTERNATIONAL

Truck Specialty Center



Escobedo, Mexico - Springfield, Ohio
<http://truckspecialtycenter.com> - 800.641.4000

Quote #: JGR001421 Quoted: 8/14/2015 Revised: Valid Till: 10/13/2015

Contact Information	Vehicle Information	
Kenny Necaise	Order:	Quote
Ward International - Pensacola	Job:	Quote
850.206.6549	Model: 5900i	Axle Config: 6x4
knecaise@bellsouth.net	Quantity: 1	Build Date: TBD

Line	Modification Description	Cost/Unit
------	--------------------------	-----------

Furnish and install a wet line kit for use with a walking floor trailer.

Includes:

- Chelsea 280 series Hot Shift PTO (for Allison 4000 RDS transmission) mounted on left side
- Parker PGP051 hydraulic pump
- 50 gallon aluminum upright tank mounted behind cab
- 2-lines to trailer (supply/return)
- hydraulic filter
- shut off valves on suction and return lines
- quick connects on for trailer line connections

01

Requires 813WCC or equivalent from factory for PTO control.

Must have sufficient space for mounting hydraulic tank or additional charges may apply.

-- Miscellaneous handling

-- Total Per Unit - Currency USD

In order for TSC to order parts and schedule work per this quote, written approval is required with the quote number and order/job numbers of the units to be worked.

Please send approval notice and/or PO to joe.reed@navistar.com and confirm unit is routed to TSCWRK.

If customer supplied parts or materials are provided on this quote, the parts or materials are required to be delivered to the TSC 10 days prior to build date. Parts and materials tracking information will be required. If parts or materials do not arrive within 10 days of the truck being received by the TSC, a storage fee of \$20.00 per day, per unit will be incurred.

All take-off parts become property of TSC unless other arrangements are made.

Thank you for considering us for this opportunity.

Quoted by: Joe Reed - 214-355-7105

<u>Description</u>	<u>(US DOLLAR)</u>	<u>Price</u>
Factory List Prices:		
Product Items	\$237,340.00	
Service Items	\$0.00	
Total Factory List Price Including Options:		\$237,340.00
Freight	\$2,200.00	
Total Freight:		\$2,200.00
Total Factory List Price Including Freight:		\$239,540.00
Less Customer Allowance:		(\$100,581.66)
Total Vehicle Price:		\$138,958.34
Total Sale Price:		\$138,958.34
Total Per Vehicle Sales Price:		\$138,958.34
Net Sales Price:		\$138,958.34

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Sales Rep. 8-14-15

 Official Title and Date

Kenny G. Pluse

 Authorized Signature

 Firm or Business Name

 Authorized Signature and Date

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.